

PRO-VAC

INDUSTRIAL PUMPOUT UNIT

Technical Specifications

Part No:	LWUNP60A10
Dimensions	24" WD X 50" LGTH x 45" HT
Weight	250 LBS
Pump	Conde ProVac Pump (35 CFM)
Motor	1-1/2 HP, 115 V, 13.4 FLA
Operating Vacuum	16" Hg
Operating Pressure	5 PSI
Pull Down Time	12 Seconds
Flow Rate	120 Gallons Per Minute
Noise Level	69 Dba @ 10 FT
Capacity @ shutoff	52 Gallons
Finish	Satin Aluminum



THE CONDE PROVAC UNIT IS AN INDUSTRIAL LIQUID WASTE VACUUM SYSTEM THAT IS IDEAL FOR GREASE TRAP PUMPING. THE PROVAC IS EXTREMELY QUIET AND PUMPS AT AN INCREDIBLE 120 GALLONS PER MINUTE. A SIMPLE FLIP OF THE SWITCH STARTS THE PROVAC IN THE VACUUM MODE FOR PUMPING. BUILT IN EXHAUST DEODORIZER KEEPS ODOR AT A MINIMUM. SIMPLY FLIP THE SWITCH TO THE PRESSURE MODE FOR OFF LOADING.

THE CONDE PROVAC INDUSTRIAL PUMPOUT UNIT IS AN INTELLIGENT SOLUTION FOR LOCATIONS NOT SUITABLE FOR "LARGE" VACUUM TRUCK HOSES. IDEAL FOR THE INDOOR REMOTE TOUGH TO GET TO JOBS. EASY TO MANEUVER, EASY TO USE, EASY TO MAINTAIN, AND IS

BUILT TO LAST.

THE CONDE PROVAC PUMPOUT UNIT IS A **PROFESSIONAL MACHINE** THAT PAYS FOR ITSELF OVER & OVER AGAIN!

WESTMOOR LTD.
906 WEST HAMILTON AVE
SHERRILL, NY 13461

WWW.WESTMOORLTD.COM

VACUUM TECHNOLOGY



PHONE: 1-800-367-0972

PRO *Condor* VAC



INDUSTRIAL PUMPOUT UNIT



RELIABLE

RUGGED

Simply its the **"BEST"**

STANDARD FEATURES:

Constructed of Lightweight Aluminum
Automatic Oiling System
1-1/2 Hp Motor (13.4 FLA)
User Friendly | Easy Access Front Controls
Hose Rack & Tool Holder
25 FT Retractable Cord Reel
Electronic Float Shutoff
Secondary Trap With Drain
24" wide Fits Through Any Standard Door
45" Height Fits Through Cargo Van Door

Liquid Filled Vacuum | Pressure Gauge
Oil Catch Muffler With Drain
Charcoal Exhaust Deodorizer
2" x 10 FT Plastiflex Suction Hose
Hand Wand Assembly
Two - 6" Cleanout Manways
Heavy Duty Wheels & Swivel Casters
Hand | Parking Brake
Vacuum & Pressure Relief Valve
Pump Flush Valve
120 Gallon Per Minute Pumping